Product Specifications

Beta® 52A Supercardioid Dynamic Kick Drum Microphone

Overview

The Shure Beta 52A is a precision-engineered dynamic microphone with a tailored frequency response and integrated swivel-mount with XLR connector designed specifically for kick drums and other bass instruments. It provides superb attack and "punch," and delivers studio quality sound even at extremely high sound pressure levels.

Features

- Premier live performance microphone with Shure quality, ruggedness, and reliability
- Modified supercardioid pick-up pattern for maximum gain before feedback and superior rejection of off-axis sound Tailored frequency response specifically shaped for kick drums and bass instruments •
- :
- Neodynium magnet for greater sensitivity and higher output Advanced pneumatic shock mount system that minimizes transmission of mechanical noise and vibration Dent-resistant, steel mesh grille and enamel coated die-cast metal construction resist wear and abuse
- •
- Studio quality performance, even at high SPL Built-in stand adapter with dynamic locking system and XLR connector simplifies setup and provides greater flexibility

Available Models

BETA 52A	Supercardioid Swivel-mount Dynamic Kick Drum Microphone with high-output Neodymium Element
Specifications	
Cartridge Type	Dynamic (moving coil)
Frequency Response	20 to 10,000 Hz
Polar Pattern	Supercardioid
Output Impedance	150 Ω
Sensitivity (at 1kHz, open circuit voltage)	-64 dBV/Pa (0.6 mV) 1 Pascal=94 dB SPL
Maximum SPL (1 kHz at 1% THD, 1kΩ load)	174 dB
Polarity	Positive pressure on diaphragm produces positive voltage on pin 2 with respect to pin 3
Weight	Net: 0.605 kg (1.35 lbs)
Connector	Three-pin professional audio (XLR), male
Case	134 dB (159 dB, -25 Pad)

R175


Beta 52A

Accessories and Replacement Parts


RK321 Replacement grille

Replacement cartridge

Polar Pattern 250 Hz 500 Hz - - - - 1000 Hz



Frequency Response





www.shure.com